

EPE-3W















INTRODUCTION

All-in-one LED emergency downlight with removable front cover design.

FEATURES

55mm/140mm trim for different cuthole applications.

Round lens for open area, oval lens for escape route.

LiFePO4 battery, long life time.


AT/MT/DALI test function.

Modular design, easy to replace each module.

Full compliant (AS/NZS 2293).

DIMENSION: mm

55mm trim plate:



140mm trim plate:

140	160	300		LED EMERGENCY Driver	
32	400		Oh.	101	
	41	Battery			
	l 	181	→		

E-mail: director@aust-tech.com.au

GENERAL		
Voltage	200-240VAC, 50/60Hz	
Lumen Output	300lm	
Mains Power	3.5W Max	
Emergency Power	3W Max	
Battery	LiFePO4 6.4V 1500mAh	
Charge Time	≥16H	
Discharge Duration	≥2H	
CCT/ CRI	5000K/ Ra>70	
Test Mode	AT / MT / DALI	
Protection Class	Class II	
IP Rating	IP20	
STRUCTURE		
Material	PC	
Operating Temp (°C)	0°C~45°C	

Round lens: C0: D63, C90: D63 Oval lens: C0: A50, C90: E63 **EM Classification Mounting Type** Recessed Mount Remarks



Phone & What's App: +61 (0) 455466450

Wechat: +86 13580389746