


Inground Filter

Quartz Sand Filter


Model: PK8017

The enclosure of inground filter is made of high quality fiberglass and polyvinyl chloride, which is strong and durable, rust-proof, low temperature resistance and anti-uv, etc. Equipped with filtering timing automatic control system and the automatic drainage system; easy to install, no need a special machine room.

Notes: Massage pump, salt chlorinator and automatic chlorine off-line feeder(Optional)



AUST TECH
ENGINEERING & SUPPLIES PTY LTD




Complete filtration
Complete circulation
Dose sterilization
Circulating water pump
Massage pump
Pressure relief valve
Pressure display
6-multi-port valve
Automatic doser
Time controller
Contactor

- Connect the outlet of the massage pump $\phi 63$
e: Connect the inlet of the massage pump $\phi 63$
f: Connect the water outlet $\phi 50$
g: Connect the sewage outlet $\phi 50$

TECHNICAL CHARACTERISTICS

Power	1HP/220V	1.5HP/220V
Filter type	Sand filter	$\Phi 525\text{mm} / \Phi 625\text{mm}$
Flow rate	12m ³ /h	16m ³ /h
External Dimension	1400×1250×1020mm	
Disinfection	Sterilizer	
Water pump	120w/220v	
Salt chlorinator	16~42 g/h	(options)
massage pump	3HP/220V	(options)
UV	65w/220v	(options)
CCOREL.250		(options)




Quartz Sand Filter

Model: PK8018

The enclosure of inground filter is made of high quality fiberglass and polyvinyl chloride, which is strong and durable, rust-proof, low temperature resistance and anti-uv light, etc. Equipped with filtering timing automatic control system and the automatic drainage system; Easy to install, no need a special machine room.

Notes: Massage pump, salt chlorinator and automatic chlorine off-line feeder(Optional)



- a: Connect the water return inlet $\Phi 50$
- b: Connect vacuum suction $\Phi 50$
- c: Connect skimmer $\Phi 50$
- d: Connect the outlet of the massage pump $\Phi 63$
- e: Connect the inlet of the massage pump $\Phi 63$
- f: Connect the water outlet $\Phi 50$
- g: Connect the sewage outlet $\Phi 50$

TECHNICAL CHARACTERISTICS

Power	2HP/220V	3HP/220V
Filter type	Sand filter	$\Phi 800\text{mm} / \Phi 900\text{mm}$
Flow rate	25m ³ /h	33m ³ /h
External Dimension	1730 x 1600 x 1280mm	
Disinfection	Sterilizer	
Water pump	120W/220V	
Salt chlorinator	16-42g/h	(options)
Massage pump	3HP/220V	(options)
CCOREL.250		(options)



(
C
D
Ci
Ma
Pre
Pre
6-m
Auto
Time
Conta



Quartz Sand Filter

Model: PK8010

In-ground filter are made of fiberglass and polyvinyl chloride, which is design and good-looking and durable. The in-ground does not need a machine house, which save construction cost, convenient operation and save maintenance cost. Multic use in-ground sand filter assemble complete set filtration configuration to high filtering capacity and to reach to back wash. According with swimming pool specifications and standards.

NOTES: Ozone and heater(optional)



TECHNICAL CHARACTERISTICS


Power

HP/220V


5mm / $\Phi 700\text{mm}$

'h

AUST TECH
ENGINEERING & SUPPLIES PTY LTD




- a: Connected the water return inlet
- b: Connected skimmer
- c: Connected suction fitting
- d: Connected the recirculating water outlet
- e: Connected backwash



Housing leakage pipe DN50

Complete filtration
Complete circulation
Dose sterilization
Circulating water pump
Pressure relief valve
Pressure display
6-multi-port valve
Automatic doser
Time controller
Contactor






Quartz Sand Filter

Model: PK8011

In-ground filter are made of fiberglass and polyvinyl chloride, which reasonable design and good-looking and durable. The in- ground does not need a machine house, which save construction cost, convenient operation and save maintenance cost. Multic use in-ground sand filter assemble complete set filtration configuration to high filtering capacity and to reach to back wash. According with swimming pool specifications and standards, it's the best choice for Big and commercail swimming pools.

NOTES: Ozone and heater(optional).




- a: Connected the water return inlet
- b: Connected skimmer
- c: Connected suction fitting
- d: Connected the recirculating water outlet
- e: Connected backwash



TECHNICAL CHARACTERISTICS

Power	2HP/220V	3HP/220V
Filter type	Sand filter	Φ800mm / Φ900mm / Φ1000mm
Flow rate	26m³/h	33m³/h 40.5m³/h
External Dimension	1650 × 1600 × 1260mm	
Disinfection	Sterilizer	



Polyester Fiber Filter

Model: PK8012

In-ground filter are made of fiberglass and polyvinyl chloride, which reasonable design and good-looking and durable. The in- ground does not need a machine house, which save construction cost, convenient operation and save maintenance cost. Multic use in-ground polyester fiber filter assemble complete set filtration configuration to high filtering capacity. According with swimming pool specifications and standards.

NOTES: Ozone and heater(optional)




TECHNICAL CHARACTERISTICS


Power	2HP/220V
Filter type	Polyester fiber filter 75ft²
	m



AUST TECH
ENGINEERING & SUPPLIES PTY LTD



- a: Connected the water return inlet
- b: Connected skimmer
- c: Connected suction fitting
- d: Connected the recirculating water outlet



Housing leakage pipe DN50




GL-002
Time control box



Inground Filter

Model: PK8019

The enclosure of wall-mounted filter is made of high quality acrylic and fiberglass, so the filter is anti-acid anti-fading, and easy to clean. Integrated filter installation without room, simple installation, convenient operation, excellent performance, thereby reducing the construction cost. It's big flow rate for 8pcs filter bag.



TECHNICAL CHARACTERISTICS



Dimensions	1370x1000x720mm
Flow rate	47m³/h
Voltage	220V / 50Hz or 60Hz
Precision of filtration bag	≤5u
Operating noise	≤50Db
Material	Fiberglass / Acrylic
Installation	Inground

EQUIPMENT

Filtration Pump	1x4HP
Filtration basket with bag	8pcs
Chlorine feeder	1pc
Time controller	1pc
4" Connection inlet	1pc

SYSTEM

Filtration system	1pc
Disinfection system	1pc
Time control system	1pc
Circle system	1pc




Quartz Sand Filter

Model: PK8015

In-ground filter are made of fiberglass and polyvinyl chloride, which reasonable design and good-looking and durable. The in- ground does not need a machine house, which save construction cost, convenient operation and save maintenance cost. Multic use in-ground sand filter assemble complete set filtration configuration to high filtering capacity and to reach to back wash. According with swimming pool specifications and standards, it's the best choice for Big and commercail swimming pools.

NOTES: Ozone and heater(optional).




- A: Connect the water return inlet, sunction fitting
- B: Connect the water outlet(after the water disinfection)
- C: Connect the water outlet(after the UV)
- D: Connect the water outlet(after the Submersible pump)
- E: Connect the water outlet(sand filter)

- 1. Water quality controller
- 2. Chlorinator feeder
- 3. Submersible pump
- 4. UV sterilizer
- 5. Water pump

TECHNICAL CHARACTERISTICS

Power	1HP/220v	1.5HP/220v
Filter type	Sand filter	Φ525mm / Φ625mm
Flow rate	12m³/h	16m³/h
External Dimension	1300x1250x960mm	
Disinfection	Sterilizer	
Water pump	120w/ 220v	
Salt chlorinator	16~42 g/h	(options)
UV	65w/220v	(options)
CCOREL.250		(options)




Quartz Sand Filter

Model: PK8016

In-ground filter are made of fiberglass and polyvinyl chloride, which reasonable design and good-looking and durable. The in- ground does not need a machine house, which save construction cost, convenient operation and save maintenance cost. Multic use in-ground polyester fiber filter assemble complete set filtration configuration to high filtering capacity. According with swimming pool specifications and standards.


NOTES: Ozone and heater(optional)




1. Filter shell
2. Sand filter
3. Chlorinator feeder
4. Water pump
5. Submersible pump

TECHNICAL CHARACTERISTICS

Power	2HP/220v	3HP/220v
Filter type	Sand filter	Φ800mm / Φ900mm
Flow rate	25m³/h	33 m³/h
External Dimension	1650x1700x1250mm	
Disinfection	Sterilizer	
Water pump	120w/ 220v	
Salt chlorinator	16~42 g/h	(optional)
UV	85w/220v	(optional)
CCOREL.250		(optional)




- A: Con junction
- B: Conne (after the
- C: Conne (after the
- D: Connect (after the S
- E: Connect (sand filter)




Quartz Sand Filter

Model: PK8013

The enclosure is made of high quality fiberglass and acrylic, which is strong and durable, rust-proof, low temperature resistance and anti-UV light, etc. Equipped with filtering timing automatic control system and the automatic drainage system; easy to install, no need a special machine room.



AUST TECH
ENGINEERING & SUPPLIES PTY LTD



TECHNICAL CHARACTERISTICS


Power	0.5HP	0.75HP	1.0HP/220v
Filter type	Sand filter	Φ400mm / Φ450mm / Φ525mm	
Flow rate	8 m³/h	10 m³/h	12 m³/h
External Dimension	950x950x950mm		
Water pump	120w/ 220v	(options)	
Disinfection	Sterilizer		

- Complete filtration
- Complete circulation
- Dose sterilization
- Circulating water pump
- Massage pump
- Pressure relief valve
- Pressure display
- 6-multi-port valve
- Automatic doser
- Time controller
- Contactor

Quartz Sand Filter


Model: PK8027

The enclosure is made of high quality fiberglass and acrylic, which is strong and durable, rust-proof, low temperature resistance and anti-UV light, etc. Equipped with filtering timing automatic control system and the automatic drainage system; easy to install, no need a special machine room. Equipped with cartridge filter inside the box, easy to operate.



1. Filter shell
2. Cartridge filtration
3. Chlorinator feeder
4. Water pump

- A: Connect the water return inlet
 B: Connect the water return inlet
 C: Connect the water outlet
 D: Connect the water outlet (cartridge filtration)



TECHNICAL CHARACTERISTICS

Power	3.0HP/220v
Filter type	Cartridge filtration AF50x3pcs
Flow rate	42m³/h
External Dimension	1450x1070x780mm
Disinfection	Sterilizer
Water pump	120w/220v (options)



Quartz Sand Filter

Model: PK8035A



- A: Connect the water return inlet, sunction fitting
 D: Connected the recirculating water outlet
 E: Connected backwash

Power	0.75HP/220V	1.0HP/220V
Filter type	Sand filter	
Flow rate		




AUST TECH
 ENGINEERING & SUPPLIES PTY LTD



- A: Connect the water return inlet, sunction fitting
 D: Connected the recirculating water outlet
 E: Connected backwash

Power	1.0HP/220V	1.5HP/220V
Filter type	Sand filter Φ525mm / Φ650mm	
Flow rate	12m³/h	16m³/h
External Dimension	1150X1100X900mm	
Chlorine feeder	CL-100	1pc
Time Controller	1pc	



Pool Massage


Model: PK8031



PK-8031A

TECHNICAL CHARACTERISTICS

Model No.	PK8031 Pool massage		
Material	Acrylic		
Dimension	2600(L)x1600(W)x1200(H)mm		
Weight			
Color	Bone color		
Power	220V/50Hz		
Flow rate	25 m³/h		
Hydrotherapy system	jet : 26pc	air jet : 30pc	s.s jet
	Circulating jet : 2pc	swim jet:1pc	
Filtering system	filter bag: 2pc		
	water return: 2pc		
	water proof box: 1200x1000x500mm		
Treatment	ozone: 1pc (500mg/h, 132W)		
Lighting	light: 2 x 18W		
Control panel	digital controller (options)		
	flow control valve (options)		
	air control valve (options)		
Pumps	filtration pump: 1 x 2HP (options)		
PK-8031A	massage pump: 2 x 3HP (options)		
	air blower: 1 x 900W (options)		
Approval	CE Certification		



AUST TECH
ENGINEERING & SUPPLIES PTY LTD